

EXPRESS 6

APPLICATIONS TABLE

Find the elevator type and verify the platform falls within the platform dimensions listed for that elevator. Next, find the intersection of the elevator's speed and capacity to confirm the roller guide is recommended for the application.

		PASSENGER CAR PLATFORM UP TO 10' WIDE X 8' DEEP/ (3050 mm X 2440 mm)					
fpm		1000	1200	1400	1600	1800	2000
SPEED							
m/s		5.0	6.0	7.0	8.0	9.0	10
CAPACITY	lbs/kg						
	≤2,500 lb 1,100 kg						
	3,000 lbs 1,400 kg						
	3,500 lbs 1,600 kg						
	4,000 lbs 1,800 kg						
	4,500 lbs 2,000 kg	Not every elevator is the same. If your application is not indicated in the red shaded area, please contact Customer Service for expert application assistance.					
	5,000 lbs 2,300 kg						
	6,000 lbs 2,700 kg						
7,000 lbs 3,200 kg							

ROLLER GUIDE RAIL COMPATIBILITY

● Compatible ○ Check Clearance

		RAIL SIZES							
ISO ASME WIDTH		T90 5/8" (16 mm)	T114 11# 5/8" (16 mm)	T125 12# 5/8" (16 mm)	T127-1 12# 5/8" (16 mm)	T127-2 15# 5/8" (16 mm)	T140-1 18# 3/4" (19 mm)	T140-2 22# 1-1/8" (28.6 mm)	T140-3 30# 1-1/4" (31.75 mm)
PART #	EX02000		●	●	●	●	●	●	●