

MODEL E

APPLICATIONS TABLE

Use the passenger car or passenger counterweight table depending on the roller guide usage. Find the intersection of the passenger car or counterweight's speed and capacity to confirm the roller guide is recommended for the application.

		PASSENGER CAR PLATFORM UP TO 10' WIDE X 8' DEEP/ (3050 mm X 2440 mm)			PASSENGER COUNTERWEIGHT		
SPEED		100	200	300	100	250	500
fpm							
m/s		0.5	1.0	1.5	0.5	1.3	2.5
CAPACITY	≤ 2,000 lbs 900 kg	●			●		
	2,500 lbs 1,100 kg						
	3,000 lbs 1,400 kg	●			●		
	3,500 lbs 1,600 kg				●		
	4,000 lbs 1,800 kg				●		
	4,500 lbs 2,000 kg				●		
<p>Not every elevator is the same. If your application is not indicated in the red shaded area, please contact ELSCO Customer Service for expert application assistance.</p> <p>● Red Polyurethane</p>							

ROLLER GUIDE RAIL COMPATIBILITY

● Compatible ○ Check Clearance

		RAIL SIZES							
ISO		T82	T89	T90	T114	T125	T127-1	T127-2	T140-1
ASME		5.75#	8#		11#	12#	12#	15#	18#
WIDTH		0.354" (9 mm)	5/8" (16 mm)	5/8" (16 mm)	5/8" (16 mm)	5/8" (16 mm)	5/8" (16 mm)	5/8" (16 mm)	3/4" (19 mm)
PART #	EE02200		●	●	●	●	●	●	